


No.	Changes and/or Note No.	Date	Sign	No.	Changes and/or Note No.	Date	Sign



UNIT: (mm)

DIMENSIONS

Size:	A	B	C	D	E	F	Part No:
15P	30.80	25.00	16.92	19.20	12.60	2.29	2101-0390-01
26P	39.20	33.30	25.25	27.70	12.60	2.29	2101-0390-02
44P	53.10	47.10	38.96	41.10	12.60	2.29	2101-0390-03
62P	69.40	63.50	55.42	57.30	12.60	2.41	2101-0390-04
78P	67.00	61.00	52.81	55.10	15.30	2.41	2101-0390-05

MATERIAL SPECIFICATIONS:

Shell: Steel, Tin Plated (Standard)

Insulator: Glass Filled PBT, UL 94 V-0

TECHNICAL SPECIFICATIONS:

Current Rating: 5 Amp

Insulator Resistance: 1000 MΩ Min.

Test Voltage: 500V AC for 1 Minute

Operating Temperature: -55°C to +105°C

DATE 2011-08-03	DRAWN MRR	SCALE	MATERIAL TYPE
	APPROVED		REPLACES



HDDBC-xx-SP
High Density Male Crimp Housing



DRAWING No.

2101-0390-0x