


This drawing must not without our, permission be copied, im-
parted to a third party or otherwise used without authorisa-
tion. Contravention will be prosecuted.

Denna ritning är vår egendom och skyddas enligt gällande lag
samt får ej utan vårt medgivande kopieras, delgivas annan eller
obehörigen användas.



TECHNICAL SPECIFICATIONS

Operating temperature -40°C to +120°C
Size: DE(09/HD 15)
1-2.Hood:
Material: ABS, UL-recognized
Cable Entry: Side
Maximum OD: 11,7
3-4.Thumbscrew: UNC 4-40 (Standard), M2,5 or M3 on request
Material: Steel
5.Plastic insert small
Material: ABS
6.Cable clamp
Material: Steel
7.Screw 2,4x7
Material: Steel
Head: Phillips
8.Screw 2,9x13
Material: Steel
Head: Phillips

REVISION	CHANGES	DATE	NAME
1	First release	2024-06-10	Idriz Musliu

Note: When ordering use Part No. in the table below


Part No. Single	Part No. BULK	Product code Single	Product code BULK	Bill of material (No.)Parts of the product
6560-0201-11	6561-0201-11	DTSL09-P-LJS-S-K	DTSL09-P-LJS-S	[1][2][3][4][5][6][7][8]

Bill of material				
No.	QTY	Part No.	Description	
1.Hood - Lower				
1	1	6805-0202-01	Plastic cover	
2.Hood - Upper				
2	1	6805-0202-11	Plastic cover	
3.Thumbscrew				
3	1	6826-0153-01	JSFM UNC 4-40	
4.Thumbscrew				
4	1	6826-0153-03	JSFM UNC 4-40	
5.Plastic insert small				
5	1	6838-0109-01	Black	
6.Cable clamp				
6	1	6830-0108-02	Cable Clamp DTSL 9 way	
7.Screw				
7	2	6855-0109-07	Screw EPS 2,4x7	
8.Screw				
8	1	6855-0112-02	CSK Self tapping screw 2 (Black)	

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE
IN MILLIMETERS

TOLERANCES UNLESS OTHERWISE SPECIFIED:
LINEAR: 0 ± 0.20
0.0 ± 0.15
0.00 ± 0.10
ANGULAR: ± 0.5°

SCALE: 1:1 SHEET 1 OF 1



encitech
A PART OF BEIJERTECH

Drawn by:	IMU
Date:	2024-06-03
Approved by	MRR
Approved date	2024-06-10
TITLE: DTSL09-P-LJS-S PLASTIC COVER	
DWG NO. 6688-9711-2	
See P/N above	
A3	